




# SMART 60

## Wood Insertion Cookers / Free standing wood cookers



Nominal power	kW	6,5
Reduced power	kW	-
Introduced thermal power (max)	kW	7,7
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	85,1
Reduced efficiency	%	-
Heating volume (min-max)	m <sup>3</sup>	156
Nominal CO at 13% O <sub>2</sub>	%	0,085
Reduced CO at 13% O <sub>2</sub>	%	-
Emissions CO (13% O <sub>2</sub> ) (min-max)	mg/Nm <sup>3</sup>	1062
Emissions OGC (13% O <sub>2</sub> ) (min-max)	mg/Nm <sup>3</sup>	64
Emissions NOX (13% O <sub>2</sub> ) (min-max)	mg/Nm <sup>3</sup>	90
Dust content at 13% O <sub>2</sub> (min-max)	mg/Nm <sup>3</sup>	21
Boiler capacity (H <sub>2</sub> O)	l	-
Hopper capacity	kg	-
Combustible		Legna
Hourly consumption (min-max)	kg/h	1,8
Autonomy (min-max)	h	-
Ignition electrical absorption (max)	W	-
Operating electrical absorption (max)	W	50
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	12
Exhaust diameter	mm	140
Combustion air inlet diameter	mm	-
Mass of smoke (min-max)	g/sec	6,3
Exhaust fumes temperature (max)	°C	185
Net weight	kg	123
Gross weight	kg	136
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-
Ducting capability up to	m	-



Art. 15A-B-VG 2015  
BlmschV 2015  
Regensburg  
München  
Stuttgart  
Aachen



### MATCH

71200010	NEUTRAL STRUCTURE	EAN 8053859012160
71200011	NEUTRAL STRUCTURE with ventilation + light kit	EAN 8053859012177
6920002	Anthracite steel	EAN 8053859012207
6920003	White steel	EAN 8053859012214
6920004	Red steel	EAN 8053859012221

### OPTIONAL

5020005	Feet	EAN 8053859012597
5020006	Podium inox	EAN 8053859012603
5020008	H4 upstand	EAN 8053859012627
5020009	H6 upstand	EAN 8053859012634
5020014	Top	EAN 8053859012689

### PLUS



Cooking



Central Top and back exhaust



Refractory stone inner with 2nd combustion air



OPTIONAL Ventilation + light kit



View on the oven



Cast iron door




Built-in



Freestanding


### STOVE PACKING



L (cm)	H (cm)	P (cm)
77	100,5	79


VOLUME (m <sup>3</sup> )
0,61

### LINING PACKING



	L (cm)	H (cm)	P (cm)
steel	60	13,5	80

### STOCKING



### TRANSPORT

